

Product images	Application	Characteristic	Structure
	► Cold/hot air suction	► Soft and gentle texture	► Color: Black
	► Chemical flue gas suction and exhaust	► Soft and easy to bend in texture	► Temperature: -40/+135 °C
	► Automotive exhaust suction	► High temperature resistance, tear resistance, and wear resistance	Can reach +150 °C in a short time
		► Resistant to most chemicals	
		► Free of plasticizers and halogenating agents	
► Hose wall: thermoplastic elastomer TPE			
► Reinforcement: Spiral steel wire			

Part Number	Internal Diameter mm	Wall Thickness mm	Weight g/m	Bending Radius mm	Working Pressure bar	Vacuum bar	Coil Length m
953-038-10	38	0.9	266	38	0.90	0.93	10
953-040-10	40	0.9	280	40	0.90	0.93	10
953-045-10	45	0.9	297	45	0.90	0.93	10
953-051-10	51	0.9	344	51	0.70	0.93	10
953-055-10	58	0.9	376	58	0.70	0.93	10
953-060-10	60	0.9	381	60	0.70	0.93	10
953-063-10	63	0.9	406	63	0.70	0.93	10
953-070-10	70	0.9	557	70	0.70	0.93	10
953-076-10	76	0.9	703	76	0.70	0.93	10
953-080-10	80	0.9	746	80	0.70	0.93	10
953-090-10	90	0.9	719	90	0.70	0.93	10
953-102-10	102	0.9	783	102	0.50	0.93	10
953-110-10	110	0.9	812	110	0.50	0.85	10
953-127-10	127	0.9	906	127	0.50	0.80	10
953-152-10	152	0.9	1093	152	0.40	0.60	10
953-160-10	160	0.9	1428	160	0.40	0.50	10
953-170-10	170	0.9	1560	170	0.40	0.50	10
953-180-10	180	0.9	1604	180	0.40	0.50	10
953-203-10	203	0.9	1779	203	0.30	0.40	10

Note: * All technical parameters are approximate values and measured under conditions of 23 °C operating temperature and 50% ambient humidity. They may change accordingly based on actual operating conditions.

* We will periodically revise or adjust the relevant parameters. If we are unable to notify in a timely manner, please forgive us and refer to the data published on the website or company.